

## Schnell ATF MV

Fully Synthetic Automatic Transmission Fluid

### Product Description:

Schnell ATF MV is a fully synthetic Automatic Transmission Fluid. Specially developed for modern automatic transmissions, hydraulic drives and power steering units. Ensures smooth gear shifting and protects against wear and tear.

### Specifications:

- GM DEXRON IIIH, IIIG, IID
- Ford Mercon V
- VW G 052 162, G 052 990, G 055 025
- VW G 055 005, G 055 162, G 052 540
- PSA AL-4
- Saab 3309
- Honda ATF Z-1
- Idemitsu K17 (JATCO)
- Aisin Warner JWS 3309
- Chrysler ATF +3, +4, MOPAR ASRC
- Mazda ATF-M III, ATF-MV
- Mitsubishi Diaqueen ATF J3, SP-II, SP-III
- Nissan 402, Nissan Matic-D, J, K
- Volvo 97340, 97341
- Volvo 4 speed (P/N 1161621), (PIN 1161540)
- Isuzu NPR ECOMAX, NPRHD, NPRXD, NQR und NRR-SCS
- Renault DP-0
- BMW 7045E, 8072B, LA 2634, LT 71141, M 1375.4
- Hyundai / KIA SP-II, SP-III, JWS 3314, JWS 3317
- KIA Red-1
- Suzuki 3314, 3317
- Toyota T, T-II, T-III, T-IV
- Subaru ATF, ATF-HP
- ZF TE-ML 03D, 05L, 09, 11A, 11B, 14A, 17C, 21L
- Allison TES-295 / -389, Allison C-4

### Typical Properties:

SAE Grade:

0W-30

Test	Method	Unit	Result
Noack Volatility	ASTM D-5800	% weight loss	11.0
Kinematic Viscosity @40°C	ASTM D445-10	cSt	32.4
Kinematic Viscosity @100°C	ASTM D445-10	cSt	6.8
Viscosity Index	ASTM D2270-04		172
Flash Point, COC	ASTM D92-05a (10)	°C	220
Pour Point	ASTM D97-09	°C	-53