

TECHNICAL DATA SHEET

Schnell RS SAE 5W40

High Performance Fully Synthetic Formula

Product Description:

Fully synthetic PAO based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. Reduces carbon or sludge build-up even under severe driving conditions. Top-class, fully synthetic fuel-economy multi-grade motor oil.

Excellently suited for use in passenger car gasoline and diesel engines, both turbo-charged and non-turbo-charged.

Specifications :

ACEA A3/B4;
 API SN/CF;
 BMW LL-01;
 MB 229.3;
 Porsche A40;
 PSA B71 2296;
 VW 502 00 / 505 00

Typical Properties:

SAE Grade:

5W40

Test	Method	Unit	Result
Density at 15°C	ASTM D4052	kg / L	0.83
Kin. Viscosity at 40°C	ASTM D445	cSt	86
Kin. Viscosity at 100°C	ASTM D445	cSt	13.5
Viscosity Index	ASTM D2270	-	167.9
Flash Point COC	ASTM D92-05A	°C	> 198
Pour Point	ASTM D97	°C	< -45

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty or representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.