

TECHNICAL DATA SHEET

Schnell DPF II SAE 5W-40

Fully Synthetic Multigrade Engine Oil - Developed for Engines with Diesel Particle Filters

Product Description:

Schnell DPF II SAE 5W-40 is a premium fully synthetic and PAO-based multigrade engine oil that protects against friction, heat and corrosion, keeping engines healthy and efficient. For use in the latest generation of passenger car gasoline and diesel engines both turbo-charged and non- turbo-charged, including vehicles equipped with diesel particulate filters (ACEA C3).

Specifications :

ACEA A3 / B4 / C3
 API SP
 BMW LL-04
 Ford WSS-M2C917-A
 GM Dexos 2
 MB 229.51
 Renault RN 0700 / RN 0710
 VW 502 00 / 505 00 / 505 01
 Fiat 9.55535-S2 / T-2

Typical Properties:

SAE Grade:

5W-40

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.843
Kinematic Viscosity @40°C	ASTM D445-10	cSt	86.9
Kinematic Viscosity @100°C	ASTM D445-10	cSt	14.1
Viscosity Index	ASTM D2270-04		170
Flash Point, COC	ASTM D92-05a (10)	°C	230
Pour Point	ASTM D97-09	°C	-34
Base Number	ASTM D2896-07a	mg KOH/g	7.5

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty or representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.